



parametre štandardných nábojov Taper Lock:

typ náboja kód	Priemer diery D v mm	Pevnosť N/m	druh Skrutiek	Hmotnosť			
				D1	typ	S	kg
1008	9 10 11 12 14 16 18 19 20 22 24 25	136	1/4" x 1/2"	35	1	22,3	0,16
1108	9 10 11 12 14 16 18 19 20 22 24 25 28*	147	1/4" x 1/2"	38	1	22,3	0,16
1210	11 12 14 16 18 19 20 22 24 25 28 30 32	407	3/8" x 5/8"	47,5	1	25,4	0,32
1215	14 19 20 24 25 28	407	3/8" x 5/8"	47,5	1	38,1	0,5
1610	14 16 18 19 20 22 24 25 28 30 32 35 38 40* 42*	486	3/8" x 5/8"	57	1	25,4	0,41
1615	14 16 18 19 20 22 24 25 28 30 32 35 38 40* 42*	486	3/8" x 5/8"	57	1	38,1	0,6
2012	14 16 18 19 20 22 24 25 28 30 32 35 38 40 42 45 48 50*	808	7/16" x 7/8"	70	1	31,8	0,75
2517	16 18 19 20 22 24 25 28 30 32 35 38 40 42 45 48 50 55 60	1310	1/2" x 1"	85,5	1	44,5	1,06
3020	25 28 30 32 35 38 40 42 45 48 50 55 60 65 70 75	2710	5/8" x 1"1/4	108	1	50,8	2,5
3030	35 38 40 42 45 48 50 55 60 65 70 75	2710	5/8" x 1"1/2	108	1	76,2	3,75
3525	35 38 40 42 45 48 50 55 60 65 70 75 80	5060	1/2" x 1"1/2	127	2	64,9	4,2
3535	35 38 40 42 45 48 50 55 60 65 70 75 80 85 90*	5060	1/2" x 1"1/2	127	2	88,9	5,13
4030	40 42 45 48 50 55 60 65 70 75 80 85 90 100*	8740	5/8" x 1"1/2	146	2	76,2	6,75
4040	40 42 45 48 50 55 60 65 70 75 80 85 90 100*	8740	5/8" x 1"3/4	146	2	101,6	7,68
4545	55 60 65 70 75 80 85 90 100*	12400	3/4" x 2"	162	2	115	10,56
5050	70 75 80 85 90 100 105 110 115 120 125	12400	7/8" x 2"1/4	177,6	2	127	15,17

parametre pre diery a drážku:

priemer diery D	drážka b	t	D*	b	t
Cez 10 do 12	4	D + 1,8			
> 12 > 17	5	D + 2,3			
> 17 > 22	6	D + 2,8			
> 22 > 30	8	D + 3,3			
> 30 > 38	10	D + 3,3			
> 38 > 44	12	D + 3,3			
> 44 > 50	14	D + 3,8			
> 50 > 58	16	D + 4,3			
> 58 > 65	18	D + 4,4			
> 65 > 75	20	D + 4,9			
> 75 > 85	22	D + 5,4			
> 85 > 95	25	D + 5,4			
> 95 > 110	28	D + 6,4			
> 110 > 130	32	D + 7,4			
			neštandardné parametre		
			28*	8	D + 1,3
			35*	10	D + 1,3
			40* / 42*	12	D + 1,3
			50*	14	D + 2,8
			90*	25	D + 3,4
			100*	28	D + 5,4